

528 Series

LCD HDTV

Models:
WD-52528
WD-62528



WD-52528 Shown

Overview

The Mitsubishi 528 Series of Integrated Digital Cable Ready LCD HDTVs feature a high quality picture in a stylish compact cabinet.

The Mitsubishi QuickMotion™ LCD drive displays sharp, crisp, and clean moving images while the SmartShutter™ system provides deeper blacks and better dark scene detail.

The 528 Series also includes a host of advanced signal processing for maximum picture quality. SharpEdge™ technology creates clean, focused edges between objects and scene backgrounds. DeepField™ imager technology dynamically adjusts brightness and contrast within every scene. And Plush720p™ upconverts lower quality signals to deliver maximum clarity from every source.

With ClearThought™ technology, digital TV becomes easy to use. The 528 Series includes two HDMI™ inputs, three component inputs, and two IEEE 1394 ports for maximum connectivity.

Get the Perfect Picture Every Time

- Mitsubishi Exclusive LCD Light Engine
- SmartShutter™
- Plush720p™
- QuickMotion™
- PerfectColor™
- Digital Cable Ready (DCR) HDTV with CableCARD™ Slot
- DeepField™ Imager (switchable)
- SharpEdge™ (switchable)

Watch TV Your Way

- TV Guide On Screen®
- NetCommand® 5.0
- 2 HDMI™ Inputs
- 3 Component Inputs
- 2 IEEE 1394 Rear Inputs
- Digital Audio Output for All Analog and A/V Sources
- Fully Illuminated Remote Control

Descriptions and specifications subject to change without notice. The dimensions are approximate for general information when deciding the locations and placements of the product. When creating a custom-built environment for this product, please take exact measurements from the specific unit to be installed before doing any finished carpentry. When installing the unit, allow for air circulation, ventilation, and variations due to manufacturing tolerances. The cosmetic appearance of the product may vary from that depicted here.

528 Series

LCD HDTV



WD-52528 Shown on Optional Matching Base

| Model | WD-52528 | WD-62528 |
|-------------------|-------------------|-------------------|
| Screen Size | 52" | 62" |
| Aspect Ratio | 16:9 (widescreen) | 16:9 (widescreen) |
| Height | 33.9" | 40.3" |
| Width | 49.6" | 58.3" |
| Depth | 17.8" | 19.9" |
| Height On Base | 51.9" | 58.4" |
| Weight | 110 lbs. | 133 lbs. |
| Power Consumption | 225 Watts | 225 Watts |

| Optical System | |
|---|-------------------|
| Light Engine | Proprietary 3LCD |
| Pixel Resolution (horizontal x vertical) | 1280 x 720 |
| LCD Driver | QuickMotion™ |
| Lamp Power | 110W |
| High Contrast System | SmartShutter™ |
| Screen Protective Shield | No |
| Video Performance | |
| Video Format Conversion | Plush720p™ |
| PerfectColor™ | • |
| DeepField™ Imager (switchable) | Yes |
| SharpEdge™ (switchable) | Yes |
| Video Noise Reduction | • |
| Picture Format Modes (4:3 sources, including anamorphic DVDs) | 6 |
| Picture Format Modes (16:9 sources) | 2 |
| User Interface | |
| Control Features | |
| TV Guide On Screen® (8-day interactive guide) | • |
| NetCommand® 5.0 Home Theater Control | • |
| IR Learning | • |
| ChannelView™ (on-screen channel list) | • |
| AV Adjustment (memorized by input/device) | • |
| Color Temperature Control (by device) | High/Low |
| Bright/Natural Mode | • |
| Full Screen Image Freeze | • |
| 2-Tuner PIP | |
| PIP Still, Exchange, and Move | • |
| Split Screen | • |
| Channel Preview | 3 POP |
| Audio | |
| Internal Loudspeakers | Stereo Full Range |
| Speaker Sizes | 5 1/2" x 2 1/4" |
| Output Power (watts/ch.) | 10W x 2 |
| Level Sound (dynamics limiter) | • |
| Digital Output (PCM) for All Analog Sources | • |
| Tuning | |
| HDTV Air/Cable (ATSC/QAM) | 1 |
| Analog Air/Cable (NTSC) | 2 |
| Digital Cable Ready (DCR) w/CableCARD™ Slot | • |
| Antenna (RF) Inputs | |
| Analog / Digital Combined | 2 |
| AV Inputs (Analog) with Stereo Audio | |
| Front A/V Inputs with S-Video | 1 |
| Rear A/V Inputs with S-Video | 2 |
| Component Video Inputs (480i/480p/720p/1080i) | 3 |

| Inputs / Outputs (Digital) | |
|--|--------------|
| HDMI™/ MonitorLink™ with DVI Stereo Audio (480i/480p/720p/1080i/PCM audio) | 2 |
| IEEE 1394 (MPEG2) Rear | 2 |
| Digital Audio Output (Dolby® Digital / PCM) | 1 (coaxial) |
| Outputs (Analog) | |
| Stereo Audio Output | 1 (fixed) |
| Independent Record AV Output | 1 |
| NetCommand® / G-Link™ IR Emitter | 2 |
| NetCommand® Remote Control | |
| Illuminated | • |
| Full Screen Remote Sensor | • |
| Customization Features | |
| Direct IR Input Selection | • |
| Direct IR Format Selection | • |
| Independent Power ON/OFF | • |
| Included Accessories | |
| Multibrand Fully-Illuminated Remote Control | • |
| IR Emitter Cable | 1 (4-headed) |
| Digital Coaxial Audio Cable | • |

Descriptions and specifications subject to change without notice.

CableCARD is a trademark of Cable Television Laboratories, Inc. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. Dolby and Dolby Digital are registered trademarks of Dolby Laboratories. DTVLink is a trademark of Consumer Electronics Association. TV GUIDE and other related marks are registered marks of Gemstar-TV Guide International, Inc. and/or one of its affiliates.

